



Tiles Adhesive

CHOOSE THE
BEST FOR THE
BETTER **RESULT**



20 Kg Bag | PACKAGING


Pro+ White

Highlights


- ✓ No Need For Hacking
- ✓ Highly Water Resistant
- ✓ Excellent Adhesion To Base Plaster/Concrete Surface
- ✓ Can Be Used On New As Well As Old Wall And Floor



HOW TO APPLY




1
Clean the surface with sand paper/putty blade & then dampen the surface.




2
Mix Tile Adhesive & water to obtain lump free paste. (Recommended mix 25-30% water)



3
After 10mins, Re-mix again for 2mins.



4
Apply first coat with putty blade.



5
With the help of notched 6mm trowel remove excess material prior placing the tiles.



6
Fix the tiles in place & tap gently with wooden hammer. Gently remove excess mixture from the tiles.

KEY FEATURES

- Suitable for interior & exterior walls
- No shrinkage
- Saves time
- High Durability
- Increases productivity
- Consistent work quality
- No curing required
- Cost-Effective

TECHNICAL INFORMATION

Sr. No	Test	Test Method	Result
1	POT LIFE	Lab Developed Method	177 MINUTES
2	WATER RETENTIVITY TEST	ASTM, C-1506-16a	NILL
3	COMPRESSIVE STRENGTH AT 14 DAYS	Compressive strength , IS: 4031 (P6)-1988 (RA-2014).	8.06 N/mm ²
4	COMPRESSIVE STRENGTH AT 28 DAYS	Compressive strength , IS: 4031 (P6)-1988 (RA-2014).	11.91N/mm ²
5	WATER CONTENT USED	-	24%

STORAGE



Storage

- ▶ Product Should Be Stored In A Dry Place Strictly Away From Moisture.

Shelf Life

- ▶ 12 Months In Unopened Packaging In A Strictly Dry And Cool Storage Place

SITARAM CHEMICALS

Add :- Block No 15. / 116, Ambika Industrial Park ,Kim Mandvi Road,
Ta : Mangrol, Dist :Surat Pin :394110
E-mail :- Sitaramchemicals12@gmail.com